

KIMERA / KIMERA RELAX



Executive and waiting armchair

Versions:

* **SMOOTH VERSION** (no stitching)



* **RHOMBOIDHAL STITCHING**



- **Executive swivel armchair:** with 5-star base on castors or feet, seat height adjustment, with fixed plate or tilting mechanism
- **Relax armchair:** with
 - 4-star chromed fixed or swivel base
 - round chromed fixed or swivel base in stainless steel Ø 580

Back and seat: monocoque shell in steel with filler in expanded cold injected fireproof polyurethane density

min. 60 Kg/m3 with extra cushion for the seat, density 40 PCM

Seat height adjustment: by gas-spring, cone Ø 28 mm.

Actions:

Fixed plate: (for version without mechanism) in black painted steel, thickness 2,5 mm., cone Ø 28 mm.

Only by request: Gas system with automatic return of the chair only for 5-star bases with glides and AL4 base without mechanism.

Tilting mechanism: structure in steel and aluminum with one-lever adjustment for:

- seat height adjustment and tilting movement control (lockable in 5 positions with anti-shock system)
- knob for tension adjustment .



“Knee-tilt” tilting mechanism: steel frame on decentralized axle, with the following adjustments:

- lever for seath height adjustment
- Lever tilt movement control 5 positions
- Back antishock system
- Tension adjustment



Bases			
	APS 5-star base in black reinforced nylon Ø 660 mm (Ansi-Bifma X5.1-1993/8)		AL7 5-star base in die-cast polished aluminum Ø 650 mm
	APG 5-star base in grey nylon Ø 675 mm		AL6 5-star base in die-cast polished aluminum Ø 654 mm
	AL9 5-star base in die-cast aluminum, aluminium grey painted Ø 650 mm		APW 5-star base in white nylon Ø 675 mm
	AL3 5-star base in die-cast polished aluminum Ø 654 mm with chromed gaslift		AL5 5-star base in die-cast polished aluminum Ø 654 mm with chromed gaslift
	AL4 (not for tilting versions) 4-star base in die-cast aluminum Ø 730 mm. with chromed feet and chromed gas-lift		AWW 5 star base in die cast aluminium white painted Ø 654 mm, with WHITE GASLIFT .
	ANN 5-star base in die cast aluminium black painted Ø 654 mm		APN 5 star base with steel inner frame 25x30 mm th.2 mm, Ø 670 mm, cover in black polypropylene. (Ansi-Bifma X5.1-1993/8)

	APP 5 star black nylon base Ø 680 with dynamic DUO glides in nylon/wood felt. For fixed versions only.		
Castors			
 040080*	for APN and AL7: self-braking soft castors Ø 50 mm	 040108* (Set n.5)	for APS, APG, APW, AL6, ANN and AL9: self-braking soft castors Ø 65 mm
 040109* (Set n.5)	for AL3 and AL5: self-braking soft castors Ø 65 mm CHROMED	 041400	for AWW: self-braking soft castors Ø 65 mm WHITE

For relax versions- waiting area:



4-star fixed or swivel frame in chromed ACC or black painted AN steel
thickness 10 mm. , Ø 770 mm. with 4 glides. Steel column Ø 50x2 mm. with fixed
welded plate thickness 5 mm. (fixed height)



**AL4 4-star base in polished die-cast aluminium Ø 730 mm. with chromed feet
and chromed gaslift. Return mechanism available.**



Swivel 4-star base in polished aluminium (AL) or black painted aluminium (AN)



round chromed fixed or swivel base in stainless steel Ø 580 mm (fixed height)

Dimensions:



MAY 2023