

KUBIX



High or low back operative chairs, visitor chairs, available with black, grey or white shells.

Seat: in reinforced nylon with filler in expanded non-deformable polyurethane, density 40 kg/m³ seat, thickness 40 mm

Backrest: in reinforced nylon, adjustable in height (65 mm) by means of an integrated mechanism with filler in expanded non deformable polyurethane, density 25 kg/m³ back, thickness 35 mm

Backrest adjustment: height adjustment (65 mm with 5 locking positions) through rack system

Covers: available colours for backrest and seat covers:

- **black**
- **light grey** (RAL 7004)
- **white**

Nylon arms colour always matches with shells colour.


Arms:



fixed arms with internal steel structure covered with injection of expanded black polyurethane



fixed arms in black, light grey or white nylon (matching with the backrest colour)



2D adjustable in nylon: adjustable in height and extensible, black, light grey or white (matching with the backrest color)



4D Adjustable, extensible, rotating and stretchable: armrests in chromed steel with cover in polypropylene, adjustable in height 100 mm. in 8 positions, extensible 70 mm in 9 positions, rotating from - 30° inner side till +30° outside, stretchable 40 mm

Seat height adjustment: through gas piston, cone $\varnothing$ 28 mm.



Mechanisms:

- **permanent contact:** fixed seat plate in black painted steel th. 2,5 mm., cone $\varnothing$ 28 mm and permanent contact system for the backrest, free floating lockable (knob lock)

- **SYNCHRON/A or SYNCHRON/S mechanism:**

steel frame with following adjustments

- button for synchron movement control
- lever to adjust the seat height
- 5 Locking position with automatic search (or free floating)
- anti shock system for the backrest
- tilting tension adjustment



- **SYNCHRON/B mechanism:** steel frame with **seat sliding system** and **attitude variator** with the following adjustments:

- button for synchron movement control
- lever to adjust the seat height
- 5 Locking position with automatic search (or free floating)
- anti shock system for the backrest
- tilting tension adjustment
- **seat sliding system** with 5 locking positions, adjustable in depth for 5 cm.
- **attitude variator** limiting the movement of the backrest forward.




Only on request: Gas system endowed with auto-return action that allows the return of the chair at the start position, only for 5-star bases with glides and AL4 base (for versions without mechanism).

Bases			
	APS 5-star base in black reinforced nylon Ø 660 mm (Ansi-Bifma X5.1-1993/8)		AL7 5-star base in die-cast polished aluminum Ø 650 mm
	APG 5-star base in grey nylon Ø 675 mm		AL6 5-star base in die-cast polished aluminum Ø 654 mm
	AL9 5-star base in die-cast aluminum, aluminium grey painted Ø 650 mm		APW 5-star base in white nylon Ø 675 mm
	AL3 5-star base in die-cast polished aluminum Ø 654 mm with chromed gaslift		AL5 5-star base in die-cast polished aluminum Ø 654 mm with chromed gaslift
	AL4 (not for tilting versions) 4-star base in die-cast aluminum Ø 730 mm. with chromed feet and chromed gas-lift		AWW 5 star base in die cast aluminium white painted Ø 654 mm, with WHITE GASLIFT .
	ANN 5-star base in die cast aluminium black painted Ø 654 mm		APN 5 star base with steel inner frame 25x30 mm th.2 mm, Ø 670 mm, cover in black polypropylene. (Ansi-Bifma X5.1-1993/8)
	APP 5 star black nylon base Ø 680 with dynamic DUO glides in nylon/wood felt. For fixed versions only.		

Fixed frame: sled frame in epoxy powder painted steel, **black and aluminum grey; or chromed**

- **Without arms** Ø 25 x 2,0 mm
- **With arms and black polyurethane top** Ø 20 x 2,0 mm

Dimensions:



February 2023