

KRUNA / KRUNA PLUS



Managerial armchair with high or medium back and visitor version.

Versions:

- With chromed frame and arms
- With white painted frame and arms
 - Seat and back fully upholstered with linear stitching
 - Seat and back fully upholstered with rhomboidal stitching



Frame: - chromed, white painted or black painted frame: external sole supporting frame in chromed steel tube mm. 30x15, thickness 2mm, with inner frame in flat steel tube mm. 30x5, and steel supporting plate thickness 5 mm.

Back and seat: fully upholstered (see fabric card) with filler in fireproof expanded polyurethane D.35 kg/m3 thickness 15 mm

Fixed arms in flat steel thickness 5 mm available in:

- full chromed, white painted or black painted steel
- chromed steel with top in black polyurethane
- chromed steel upholstered on the top

Seat height adjustment: through gas piston, cone $\varnothing$ 28 mm.

Only on request: Gas system with automatic return of the chair only for 5-star bases with glides and AL4 base without mechanism.

Mechanisms:

- **Fixed plate:** (for fixed version) in black painted steel with aluminum cone for gaslift, thickness 5 mm, $\varnothing$ 28 mm
- **Tilting mechanism "L":** steel frame with the following adjustments:
 - one lever adjustment for seat height and for locking/unlocking movements in 5 positions, with anti-return system for the backrest
 - tilting tension adjustment



- “knee-tilt” “N” mechanism with polished aluminum cover: aluminum frame with tilting on decentralized axel, with the following adjustments:



- lever for seat height adjustment
- lever for locking and unlocking the tilting in 4 positions
- anti-return system for the backrest
- tilting tension adjustment

Bases			
	APS 5-star base in black reinforced nylon Ø 660 mm (Ansi-Bifma X5.1-1993/8)		AL7 5-star base in die-cast polished aluminum Ø 650 mm
	APG 5-star base in grey nylon Ø 675 mm		AL6 5-star base in die-cast polished aluminum Ø 654 mm
	AL9 5-star base in die-cast aluminum, aluminium grey painted Ø 650 mm		APW 5-star base in white nylon Ø 675 mm
	AL3 5-star base in die-cast polished aluminum Ø 654 mm with chromed gaslift		AL5 5-star base in die-cast polished aluminum Ø 654 mm with chromed gaslift
	AL4 (not for tilting versions) 4-star base in die-cast aluminum Ø 730 mm. with chromed feet and chromed gas-lift		AWW 5 star base in die cast aluminium white painted Ø 654 mm, with WHITE GASLIFT .
	ANN 5-star base in die cast aluminium black painted Ø 654 mm		APN 5 star base with steel inner frame 25x30 mm th.2 mm, Ø 670 mm, cover in black polypropylene. (Ansi-Bifma X5.1-1993/8)
	APP 5 star black nylon base Ø 680 with dynamic DUO glides in nylon/wood felt. For fixed versions only.		

Castors			
 040080*	for AL7: soft braked castors Ø 50 mm	 040108* (Set n.5)	for APS, APG, APW, AL6, ANN and AL9: soft braked castors Ø 65 mm
 040109* (Set n.5)	for AL3 e AL5: soft braked CHROMED castors Ø 65 mm	 041400	for AWW: soft braked WHITE castors Ø 65 mm

Fixed frames: sled base with arms in ovalized chromed steel tube Ø 25 mm.

Dimensions:



April 2021